

Rusta Oil paint Tradition

Product description:

Oil paint for fences, doors, outdoor furniture, building façades, etc. A classic naphtha-based combination of alkyd and boiled linseed oil that provides good protection and penetration. For painting on fresh wood or wood previously painted with oil paint or glaze.

TECHNICAL DATA:

Use	Exterior
Binder	Alkyd
Volume solid	34%
Weight solid	47%
Density	1.095 kg/l
Gloss	Semi-gloss
Washability	Class 1 (EN 13300)
Cleaning/dilution	White spirits
Material consumption	5–8 m ² /l sawn timber, 10–15 m ² /l planed timber
Air/surface temperature when painting	Minimum +5°C
Painting tool	Paint brush
Touch dry	8 h
Paintable	24 h
Completely dry	48-72 h
Shade	White
Flammability	3
VOC category	(Cat. A/e): 400 g/l

Rusta Oil paint Tradition

Instructions:

Preparation

The surface to be painted must be clean, dry and firm. Scrape away any loose paint from previously painted surfaces. Wash previously painted surfaces with façade and mould wash and rinse well. If the surface is infested with mould, it should be treated with a disinfectant. Untreated timber should be primed with Oil paint Tradition diluted with 10-15% white spirits.

Application

Apply the paint with a dense brush and work the paint well into the surface. It is best to paint several thin layers every few days rather than one thick layer. Suitable weather for painting is important for good results. Do not paint during prolonged cold or humid weather and avoid painting on hot or sunlit surfaces.

Moisture and dew after painting can cause dull or blotchy surfaces.