## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Rusta

Supplier's address: Rusta AB, Kanalvägen 12, 194 61 Upplands Väsby, SE

Model identifier: 911501750101

## Type of light source:

Colour-tuneable light source: High luminance light source:	No No	Envelope:	-
		source (CLS):	
Mains or non-mains:	MLS	Connected light	No
(or other electric interface)			
Light source cap-type	E27		
Lighting technology used:	LED	Non-directional or directional:	NDLS

Flouder parameters					
	Value	Parameter	Value		
General product parameters:					
nption in on- 00 h), rounded st integer	3	Energy efficiency class	F		
s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	300 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 700		
ver (P <sub>on</sub> ), ex-	3,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Height	125	Spectral power dis-	See image		
Width Depth	80 80	tribution in the range 250 nm to 800 nm, at full-load	in last page		
	00 h), rounded st integer s flux (¢use), in- ers to the flux in , in a wide cone arrow cone (90º) ver (Pon), ex- tandby power expressed in W the second dec- Height Width	ValueGeneral product pnption in on- 00 h), rounded st integers flux (\$\phiuse\$), in- ers to the flux in , in a wide cone mrrow cone (90°)ver (P_on), ex- expressed in W the second dec-Height125 Width	ValueParameterGeneral product parameters:mption in on- 00 h), rounded st integer3Energy efficiency classs flux (фuse), in- ers to the flux in , in a wide cone prrow cone (90°)300 in Sphere (360°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setver (Pon), ex-3,0Standby power (Psb), expressed in W the second dec-tandby power expressed in W the second decColour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be setHeight125Spectral power dis- tribution in the range 250 nm to 800		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi- nates (x and y)	0,466 0,425		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	10	Survival factor	1,00		
the lumen maintenance factor	0,99				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,98	Colour consistency in McAdam ellipses	3		
Claims that an LED light source replaces a fluorescent light source without integrated bal- last of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

## Spectrum : High

