Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Rusta	Э
--------------------------------------	---

Supplier's address: Rusta AB, Kanalvägen 12, 194 61 Upplands Väsby, SE

Model identifier: 911501920101

	Type of	ilight	source:
--	---------	--------	---------

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	E27				
(or other electric interface)					
Mains or non-mains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded	4	Energy efficiency class	F		

mode (KWII) 1000 III, Tourided		Class		
up to the nearest integer				
Useful luminous flux (фuse), in-	400 in	Correlated	colour	2 700
dicating if it refers to the flux in	Sphere (360°)	temperature	,	

a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)		rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power (P _{on}), ex- pressed in W	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	<u>-</u>
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or	80

imal			the range of CRI-val- ues that can be set	
Outer dimen-	Height	106	Spectral power dis-	See image
sions without	vviacii	60	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	60	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,463
		nates (x and y)	0,418
Parameters for LED and OLED li	ght sources:		
R9 colour rendering index value	9	Survival factor	1,00
the lumen maintenance factor	0,99		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	1,00	Colour consistency in McAdam ellipses	2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)'-': not applicable; (b)'-': not applicable;

Spectrum : High

