## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's na	ime or trade	e mark:	Rusta
---------------	--------------	---------	-------

Supplier's address: Rusta AB, Kanalvägen 12, 194 61 Upplands Väsby, SE

Model identifier: 911501940101

_	•			
Type	Λt	light	COLL	rco.
IVDE	VI.	HEILL	3UU	ıce.

Type of light source:			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			

Product parameters				
Parameter		Value	Parameter	Value
	General product parameters:			
Energy consummode (kWh/10 up to the neares	00 h), rounded	4	Energy efficiency class	F
dicating if it refe a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone rrow cone (90º)	400 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	4,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	_
(P <sub>net</sub> ) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80
Outer dimen-	Height	143	Spectral power dis-	See image
sions without	Width	64	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	64	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,461 0,420
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	3	Survival factor	1,00
the lumen maintenance factor	0,99		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	1,00	Colour consistency in McAdam ellipses	2
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0

(a)'-': not applicable; (b)'-': not applicable;

## Spectrum : High

